



Marquis 3000MWB

Single Line Basic



Features

- Single Line Operation
- Message Waiting Visual indicator - no TouchLite
- Full Length Custom-tailored Faceplate
- HAC Volume Control
- Electronic Ringer with Hi/Low Volume adjustment
- Data Port
- Compact Low Profile Design
- Durable matte-finished design
- Desk or Wall mountable with optional bracket

Technical Specifications

- Line Voltage - 24-52 VDC (+/-)
- Operating Current - 20mA-100mA
- Message Waiting - High voltage 90VDC, Low Voltage LED
- Ringer Equivalence - 0.8B
- Volume Control - 12-15dB gain
- FCC/ETL Registered - Compliant
- Hearing Aid Compliant - Yes
- Installation - RJ14 (USOC) Fully Modular, Telephone Line Cord 15'4.5m, Handset Coil Cord 9'2.25m

Product Information Specifications

- Model Number
 - 3000MWB - 36039 (Ash)
 - 3000MWB - 360391 (Black)
- Standard Colors Ash & Black - custom colors are available in min. quantities of 500
- Unit Dimensions 9.75" (l) 6.5"(w) 3.25"(h)
24.38cm(l) 16.25cm(w) 8.13cm(h)
- Packaging Wt. MasterPack quantity of 10 units, weight is 27lbs, 12.25kg

TeleMatrix, Inc. 5025 Galley Road, Colorado Springs, CO 80915
1.800.462.9446 toll free (USA & Canada) - **719.638.8821** tel., **719.638.8815** fax.